

Allan Padelord

CAMERA CARS

the edge CRANE SPECS

BOOM LENGTH: SIX DIFFERENT LENGTH OPTIONS
RANGING FROM 8 TO 26 FEET

BOOM ROTATION: 360*

360* PAN ROTATION: 4.5 SECONDS

PAN SPEED: 70* PER SECOND

TILT SPEED: 70* PER SECOND

TILT RANGE: 120*

MAXIMUM PAYLOAD

(HEAD AND CRANE COMBINED)

220 LBS. (WITH BOOM LENGTH UP TO 18")

110 LBS. (WITH BOOM LENGTH 22'-26')

CRANE WEIGHT: 750 LBS STABILIZATION:

MAXIMUM HEIGHT

WITH STANDARD EXTENSION: 13'8" WITH 15' BOOM LENGTH

WITH LONGEST EXTENSION: 23.0' WITH 26' BOOM LENGTH

MINIMUM LENS HEIGHT: MINUS 10 FEET

MAXIMUM LENS HEIGHT: 23 FEET

MINIMUM CLEARANCE: 10FT 4IN. (ON ESCALADE)

MAXIMUM VEHICLE SPEED WITH CRANE: UP TO 120MPH

VARIES BY SITUATION

OPERATING TEMPERATURE RANGE: -30°F TO +130°F

POWER SUPPLY: DC

CAMERA ACCESSORY POWER SUPPLIES: 12V, 24V, 30V

CRANE BALANCE: COUNTER BALANCE WITH SHOT BAGS

SETUP TIME: CAMERA READY IN 5 MINUTES

EXTENSION BUILD TIME: 30 MINUTES FOR 4FT. SECTION

1.30 MINUTES FOR 8FT. SECTION

BOOM LOCK: PAN AND TILT

WWW.APCAMCARS.COM

661.268.1330

